ΔVIGILON Smart Readers

Expandable Access Control for the Modern Workplace



Some hardware may show the Openpath logo

OP-R2X-STND, OP-R2X-MULL

The Avigilon Smart Reader leverages industry-leading security combined with an elegant design that will enhance any door and office environment. The Smart Reader v2 is a multi-technology reader that supports mobile and card credentials, and low (125 kHz) and high (13.56 MHz) RFID frequencies. The Avigilon Smart Readers are available in a Standard or Mullion form-factor, making them ideal for any entry. They work seamlessly with the cloud-native Avigilon Alta Control Center, providing visibility and management from anywhere.



Get Up and Running Faster

Sleek form factor is easy to mount and install with standard electric wiring. Flexible mounting options to suit a variety of deployment needs, indoors and out.



Easy Management and Monitoring

Software runs in the cloud for easy, secure access and remote monitoring, without the need for local servers. Built-in diagnostics and real-time troubleshooting insights streamline management.



Intuitive Design

Multiple LEDs provide visual indicators of Reader state, displaying conditions for configurations and connectivity as well as access and entry status.



Fast, Reliable Mobile Access

Patented Triple Unlock with Bluetooth, WiFi and cellular data ensures reliable unlocks, with mobile credential options like Wave to Unlock, and mobile or watch app.



Protected and Fail Safe

Tamper resistant, and designed to withstand power failures and internet outages. Readers store no data, and encrypted end-to-end communication and strong public-key cryptography to keep everything protected.



Lifetime Limited Warranty

Ensure peace of mind, knowing that Avigilon stands behind its access control hardware with a lifetime limited warranty, guaranteeing the quality of your security solution.

For more information, visit <u>avigilon.com/access-control/standard-smart-reader</u> and <u>avigilon.com/access-control/mullion-smart-reader</u>.

Specifications

Compatibility

Mobile Credential Bluetooth LE

NFC (Android only) Auto Proximity Unlock Wave to Unlock

Supported on iOS and Android™ compatible devices

High-Frequency (13.56 MHz)

Cards and Fob*

Avigilon DESFire® EV3 Smart Card Avigilon MIFARE® Classic 1K Fob

MIFARE Classic, DESFire, Ultralight (ISO14443A) CSN

Low-Frequency (125 MHz)

Card and Fob

Avigilon Proximity Card Avigilon Proximity Fob

HID® Proximity™, ProxCard®, LenelProx®

^{*}The discontinued Openpath EV1 and EV2 cards are still compatible. The EV3-A card is still referred to as the Openpath DESFire EV3 Smart Card. IOS is a trademark of Apple Inc. Android is a trademark of Google LLC.

General		
LED Indicators	Reader power on or off, user access granted or denied, entry or door locked or unlocked, provisioning and connection status to access control system	
Wiring	RS-485 to connect to Avigilon expansion boards and Wiegand inputs for third-party devices Pigtail Length: 12 in (305 mm)	
Power	0.25A @ 12VDC 0.12A @ 24VDC	

Dimensions OP-R2X-STND OP-R2X-MULL Device Only With surface mount bracket* 0.87 in 0.43 in 0.85 in (22 mm) (11 mm) (22 mm) 4.69 in 4.72 in (119 mm) (120 mm) 2.91 in (74 mm) 1.77 in (45 mm) Flush mount in US gang box (recommended) Surface mount on wall or door frame



Dimensions OP-R2X-STND OP-R2X-MULL Included Surface Bracket OP-R2X-MULL None Via mm) OP-R2X-MULL None Via mm) OP-R2X-MULL None OP-R2X-MUL

Environmental		
Temperature	Operating Temperature: -30°C (-22°F) to 60°C (140°F)	
Humidity	Operating Humidity: 5% to 85% relative, non-condensing	
IP Rating	Indoor and Outdoor: IP65 (IEC 60529)	

Operating temperature must not be exceeded.

Regulatory	
Certifications	FCC (United States), IC (Canada), CE (Europe), UKCA (United Kingdom), NOM (Mexico), BIS (India), UL 294, RoHS
Compliance	NDAA, TAA

Warranty

Avigilon Alta Access Warranty Lifetime limited; for more information, visit avigilon.com/support/warranty



Ordering Information

Part Number	Description
OP-RKP-MULL	Avigilon Smart Reader v2- Mullion Form Factor - Black
OP-RKP-STND	Avigilon Smart Reader v2 - Standard Form Factor - Black
OP-CVR-W	White Front Cover for Avigilon Smart Reader v2 - Standard Form Factor

.

For more information, contact:



info@erswireless.com 800-475-3320



